

N90-10167

527-36

Beamed Laser Power in Support of Near-Earth Missions

SC- J. 4/10


ND 2 10491

Edmund Conway
Gregory Schuster
Willard Weaver
Donald Humes

NASA Langley Research Center


Reference Missions

BEAMED LASER POWER IN SUPPORT OF NEAR EARTH MISSIONS Reference Missions



ORIGINAL PAGE
BLACK AND WHITE PHOTOGRAPH

125 KW SPACE STATION
(Lunar Observatory Accomodation)
(75 KW PV +50 KW SD)
(NASA TM-4750)



LASER-BEAMED POWER VS. CONVENTIONAL POWER

Conventional Technologies

- Photovoltaic power generators (including batteries) add mass and produce atmospheric drag. This drag requires space station to be reboosted.
- Solar Dynamic power generators produce less atmospheric drag than PV.

Approach

- Remove conventional power generators and do not carry to LEO reboost fuel.
- Place laser converter, radiator and batteries on space station.
- Provide laser power.
- Since earth-to-orbit launch is very costly (\$/Kg), we will compare power options in terms of total mass taken over 10 years to LEO (TMLEO/10 yrs.) to meet the space station's power requirements.

Comparison

- Is beamed power (a) better than conventional, (b) competitive, or (c) not competitive?
- If beamed power is better, we will know what could have been gained if the technology had been developed earlier.

SPACE STATION POWER SYSTEM MASSES

(10 years, on-board power generation)

1. All Photovoltaic Power


$$P_{ss_1} (N) = N * 75: \text{ KWe}$$

$$M_1 = N * M (75 \text{ KW PV}) + M (\text{FUEL}_1): \text{ Kg}$$


2. 75 KW PV + Solar Dynamic

$$P_{ss_2} (N) = 75 + N * 25: \text{ KWe}$$


$$M_2 (N) = M (75 \text{ KW PV}) + N * M (25 \text{ KW SD}) + M (\text{FUEL } 2): \text{ Kg}$$




SPACE STATION POWERED BY SOLAR-PUMPED LASER




PRELIMINARY CONCEPT STUDY
OF
SOLAR-PUMPED LASER POWER
BEAMED TO SPACE STATION



ONE MEGAWATT IODINE SOLAR PUMPED LASER POWER STATION



POWER RELAY SATELLITE (JPL D-1919)




ACTIVE COOLING


ACS SIZED FOR
10 YEARS

ADAPTIVE OPTICS
(30 kg/m²)


LASER ENERGY-SEMICONDUCTOR BAND GAP ENERGY COMPARISON




SCHEMATIC DIAGRAM OF CONVERTER LASER BEAM




LASER PHOTOVOLTAIC CONVERSION SYSTEM





**Relative Subsystem Masses
for
Laser Power Beamed to Space Station**




Space Station Beamed-Power-System Mass



TWO CONVENTIONALLY POWERED SPACE STATIONS



A Laser Supported Space Station Concept



SUMMARY

• *It has been* Solar-pumped laser-beamed power:

- *is* Lighter than photovoltaic for power requirements of 150 KWe and above; *and is*
- *is* Competitive with combined photovoltaic/solar-dynamic over the entire power range investigated.

• *A* Space Station supported by laser-beamed power:

- Can be a lower-g facility (reduced drag) than with PV or PV + SD power;
- Has greater freedom of orientation (small receiver moves rather than large arrays or concentrators); *and*
- Requires less structure (arrays, alpha joints, booms) permitting easier control and fewer vibrational modes.

CONCLUSION

- Laser power beaming offers a revolutionary concept for planing, designing, and powering large orbiting spacecraft.